

PRODUCT DATASHEET

Plastowax-R220

PRODUCT DESCRIPTION

Plastowax-R220 is a consistent lubricant, mixture of liquid and solid hydrocarbons.

FIELD of APPLICATION

Plastowax-R220 can be applied as slider material in rubber industry.

Application technology:

Plastowax-R220 is suggested to be used by EDPM type mixtures in 1-4 phr ratio. By procedure the power consumption decreases, Plastowax-R220 conduces to process the mixture of rubber and makes the surface shiny.

It is practical to heat up the product to a temperature 10-15 °C above its dropping point.

PROPERTIES and SPECIFICATIONS

Property and Unit	Requirement	Method
ASTM colour number, max.	0,5	ASTM D 1500
Density at 70 °C, g/cm ³	0,835	ASTM D 1298
Viscosity at 100 °C, mm ² /s	8 - 11	ASTM D 445
Drop melting point, °C	4 8- 60	ASTM D 127
Cone penetration at 25 °C, 0,1 mm	130 - 180	ASTM D 937
Flash point (Cl), °C, min.	220	ASTM D 92

PACKAGING and LABELLING

In new green iron drums of 175 kgs/net, inside not painted, palletized. Non-returnable drums. Labelling is with white dye.

The product is also available in heated road tank car and metal cans of 18 kgs/net (=23 litres).

STORAGE CONDITIONS

It is recommended to store Plastowax-R220 under roof or indoor, protected from direct sunshine and precipitation. If properly stored the product meets the quality requirements for 2 years from the date of production. Fire Hazard Class; IV.

<u>SAFETY</u>

By its storage, usage and transportation safety measures related to petroleum product should be observed.



ISO 9001 - ISO 14001

a member of Prista Oil Group



PRODUCER and EXPORTER

For special requirements please contact the producer and exporter:

Production plant:

BOGDÁNY PETROL Ltd. H-4511 Nyírbogdány Gyártelep HUNGARY

Phone: +36-42/232-377 Fax: +36-42/232-227 Export Sales Office:

BOGDANY PETROL Ltd. H-1117 Budapest Fehérvári út 84/A. HUNGARY

Phone: +36-1/324-2101 Fax: +36-1/324-2102 Email: <u>export@bogdanypetrol.hu</u>



ISO 9001 - ISO 14001

a member of Prista Oil Group