

PRODUCT DATASHEET

Plastowax-R200

PRODUCT DESCRIPTION

Plastowax-R200 is a yellowish brown, wax-like material, a mixture of microcrystalline paraffin and polyethylene.

FIELD of APPLICATION

Plastowax-R200 is suitable for the substitution of polyethylenes with low molecular weight, where the simple processing on low temperature is important. Plastowax-R200 is advantageously applicable as emollient, inner slider in rubber industry.

Application technology:

Plastowax-R200 can be easily mixed into rubber at temperature above its dropping point.

PROPERTIES and SPECIFICATIONS

Properties and Unit	Requirement	Method
Appearance	yellowish brown wax	visual
Viscosity at 100 °C, mm ² /s	155 – 185	MSZ EN ISO 3104
Dropping point, °C	85 - 110	MSZ 09-60.0135
Water content, % (m/m)	free	MSZ EN ISO 9029

PACKAGING and LABELLING

Pastellized packed in paper sacks.

STORAGE CONDITIONS

Plastowax-R200 is suggested to be stored far from bright sunshine, dust and precipitation, at room temperature.

In case of proper storage the product will keep its quality for 2 years counting from the date of production.

Fire Hazard Class: IV.

SAFETY

By its storage, usage and transportation safety measures related to petroleum product should be observed.



ISO 9001 – ISO 14001

a member of Prista Oil Group

PRODUCER and EXPORTER

For special requirements please contact the producer and exporter:

Production plant:

BOGDÁNY PETROL Ltd.
H-4511 Nyírbogdány
Gyártelep
HUNGARY

Phone: +36-42/232-377

Fax: +36-42/232-227

Export Sales Office:

BOGDANY PETROL Ltd.
H-1117 Budapest
Fehérvári út 84/A.
HUNGARY

Phone: +36-1/324-2101

Fax: +36-1/324-2102

Email: export@bogdanypetrol.hu



ISO 9001 – ISO 14001

a member of Prista Oil Group